



Black Bearing

			C (crankset diameter)			
			B (frame width)	24 & GXP (adaptor)	DUB (29 mm)	30
A (frame diameter)	to screw	BSA / BSC	68 / 73	BSA-68/73-24/GXP...  	BSA-68/73-DUB...  	BSA-68/73-30...  
		T47	68 / 73	T47-68/73-24/GXP...  	T47-68/73-DUB...  	T47-68/73-30...  
			86 / 92	T47-86/92-24/GXP...  	T47-86/92-DUB...  	T47-86/92-30...  
		ITA	68 / 73	ITA-68/73-24/GXP...  	ITA-68/73-DUB...  	ITA-68/73-30...  
	to press	41	86 / 92	41-86/92-24/GXP...   	41-86/92-24/DUB...	41-86/92-30...
		42	68 / 73	42-68/73-24/GXP...   	42-68/73-DUB...   	42-68/73-30...   
		46	68 / 73	46-68/73-24/GXP...   	46-68/73-DUB...   	46-68/73-30...   
			79	46-79-24/GXP...  		
			68 / 92	46-86/86-24/GXP...   	46-86/86-DUB...   	46-86/86-30...   



aluminium cup



interchangeable bearing



bb lock technology



deliver without tool : standart shimano hollowtech



deliver with Blackbearing tool



No tool -bottom bracket to press